



LEADING TODAY WITH THE BEST IN CLASS LEO TERMINALS



KYMETA

onnected by One Wel

KEY FEATURES

Low power

Easy installation

Native mobility support Low profile and light weight

Full duplex in single RX/TX aperture

USES

Fixed sites

Portable solutions

Comms-on-the-move

Comms-on-the-pause

Ubiquitous connectivity

MARKETS

VVIPs

Energy

Government

On-road fleets

First responders

Law enforcement

Industrial enterprise



SPECIFICATIONS*

TERMINAL TYPE	OneWeb	OneWeb-LTE	
Antenna type	Full duplex, single aperture, Ku-band flat-panel antenna, electronically steered holographic beamforming array		
Scan angles	Azimuth: 360°, Elevation: +15° to +90°		
Polarization	Circular, software-defined		
Receive (RX) band	10.70 GHz to 12.75 GHz		
RX throughput	Up to 195 Mbps		
Transmit (TX) band	14.00 GHz to 14.50 GHz		
TX throughput	Up to 32 Mbps		
Satellite modem	Embedded	Embedded OneWeb	
Cellular modem	N/A	600 Mbps (LTE-A Pro) (Global or FirstNet configurations)	
Interfaces	Ethernet	Ethernet & Wi-Fi (802.11b/g/n)	
Dimensions	L 89.5 cm × W 89.5 cm × H 14 cm / L 35.2 in. × W 35.2 in. × H 5.5 in.		
Weight	30.1 kg / 66 lb.	31.1 kg / 68 lb.	
Input power	12 VDC to 36 VDC or 90 VAC to 305 VAC via an accessory		
Power (typical, steady state)**	95 W	125 W	
Operational temp	-40 °C to +55 °C		
Storage temp	-40 °C to +85 °C		
Ingress protection	IP66		
Compliance	CE, FCC, Nemko, WEEE, RoHS		

ALL TERMINAL VERSIONS ARE ALSO AVAILABLE IN GO CONFIGURATIONS





AVAILABLE ACCESSORIES

- » AC-to-DC power kit
- » u8 DC power kit
- » Fixed mount
- » Vehicle rack mount (coming soon)
- » Transport case
- » GO system:
 - » Rugged transport case with built-in tie-down points and drainage for rapid water egress
 - » AC-to-DC universal power kit included
 - » Vehicle mount included
 - » Universal clamp mount

^{**}Software-controlled peak power draw. User-configurable to a higher threshold for very low-temperature operation. WARRANTY VOIDED IF THE HAWK US IS USED IN A MARITIME ENVIRONMENT.













For more information, contact Kymeta at sales@kymetacorp.com

^{*}Specifications as of March 2023. Subject to change.