





# TV & SPECTRUM ANALYZERS


www.promaxelectronics.com












## **HEVC H.265 compatible**

High efficiency Video Codec







**ULTRA FAST SPECTRUM** 




TRIPLE SPLIT DISPLAY



LIGHT WEIGHT (< 3 kg)



SMART BATTERY CONTROL ©









### For broadcasters

#### Network delay margin 🌣

Network planners determine what time instant transmitters should use to broadcast the transport stream bits. They all have to do it at a precise given time, e.g. 700 ms in the picture. The difference between the network delay and the required transmission time (700 ms in the example) is called the "network delay margin" and it will be different depending on the specific transmitter location. The lower the 'network delay margin' the higher the chances of that particular transmitter missing the assigned transmission time.





#### Receiving and analyzing T2-MI signals o

T2-MI is the modulator interface signal used in the 2nd generation digital terrestrial television broadcasting system. It is physically transported to the TV towers using IP or RF and it is accessible via network devices in the form of ASI or IP signals.

**RANGERNeo** can receive a T2-MI signal via RF, ASI and IP, in which case it can perform transport quality measurements, T2-MI packet analysis and PSI extraction from each PLP.







# Professional spectrum analyzer

#### **Reference traces**

Freeze the spectrum graph and compare it with the running trace. Save that information and use it to identify satellites based on their spectrum footprint.






#### **Triple split display**

Up to 9 different ways to combine TV, measurement and spectrum modes.







## High resolution filters \*

#### **Touch screen**

Place the marker on any channel and move the trace using your finger. Enter frequencies or file names using the soft keypad.






#### MIN and MAX hold

Display them separately or simultaneously along with the current spectrum trace.







## 2.4 & 5.7 GHz WiFi analyzer &

### Simultaneous real spectrum analyzer information + WiFi access point data

WiFi signals can be disturbed by interference from other WiFi stations, for example other access points, but also from non-WiFi signals such as wireless CCTV cameras or a microwave oven. **RANGER**\*Neo\* can display real spectrum analyzer information and access point data simultaneously.






#### **Access point information**

**RANGERNeo** shows convenient information from the access points such as SSID, RSSI, SNR, security information, etc. It also indicates the number of access points per channel and offers you guidance regarding the level of occupancy of a specific channel.






### Productivity tools

#### **StealthID**

The **RANGER**Neo StealthID function automatically identifies the required demodulation settings while tuning so that you don't need any previous information about the signal.





#### **Full band power**

The measurement of full band power is very useful to understand how much energy is available in total at the test point.





The webControl is an operating mode of the RANGER Neo field strength meter that enables its remote control via a local area network (LAN) or the Internet. Thus, it is possible to log into the equipment from anywhere in the world at any time.



#### **MEASUREMENTS AND SPECTRUM**

Tuning parameters, real time navigation and adjustment of the spectrum, channel measurements....



#### TV PARAMETERS

Streaming of a TV/radio service, displaying information, recording the TS or the service...



#### **MONITORING**

Monitoring the quality parameters, setting alarms and pre-alarms, e-mail warnings...




#### **HISTORICAL MONITORING**

Displaying a measurement graph, reviewing the measurements, exporting data to CSV...



#### **INSTALLATIONS MANAGEMENT**

Uploading and downloading files from the internal memory of the equipment or the connected USB storage media.







#### RANGER*Neo* Console

Complete control over your field strength meter from anywhere in the world and with no additional software installation required. A virtual platform that gives you access to all of the analyzer features.





#### **Video / Audio Streaming**

It is now possible to stream the Transport Stream after channel demodulation either over a private LAN or over the Internet, as a unicast (UDP) stream. The service as seen on the analyzer screen can be streamed as a SPTS over IP, or as a full TS containing all services for the channel being tuned.

The same feature can be used for other streams received over IP or previously recorded, instead of coming from an RF source.





#### PROWATCH Neo

**PROWATCH** *Neo* is our response to the need for remote, permanent, 24/7 signal monitoring operations. It is embedded in a 19" 1U rack case and it allows you to do everything you can do with the portable analyzers but remotely. It is also possible to connect it to a keyboard and monitor using USB and HDMI™ interfaces.






#### **Professional monitoring system**

**PROWATCH** Neo is a professional monitoring system based in the **RANGER** Neo technology allowing users to perform:

- Live transport stream and service recording.
- Service IP streaming.
- · Alarm generation.
- · Service quality and alarm statistics.







## Many useful functions

#### Merogram and Spectrogram ○

These functions have been developed to allow an early detection of intermittent impairments that may occur in very short periods of time and can not be monitored otherwise.






#### **Attenuation test**

Test the frequency response of your installation using RP-050, RP-080, RP-110B signal generators.







## Constellation diagram

Detecting signal impairments at a glance

#### 16/32 APSK, 8PSK and QPSK constellation

In the case of an ideal transmission channel, free of noise and interferences, all symbols are recognized by the demodulator without errors. In this case, they are represented in the constellation diagram as well defined points hitting in the same area and forming a clear dot.






#### 16. 32. 64. 128. 256 OAM O

Every modulation type is represented differently. A ITU J.83 Annex B 16QAM signal is represented on the screen by a total of 16 different zones, and a DVB-C 64QAM is represented on the screen by a total of 64 different zones and so on.







#### **Network bitrate**

The network bitrate gives you an indication of the network load and possibility of overload.

#### **Multicast Media Delivery Index and FEC**

A key quality measurement formed by the Delay Factor and the Media Loss Rate. FEC measurements are also available.

#### **IP Ethernet frame viewer**

IP Ethernet frame viewer captures a multicast packet displaying all its frame details, for example Time-To-Live (TTL), all fields of RTP protocol, etc. It is very helpful to study IPTV signalisation problems.

#### PING, Trace, Average packet delay and IPDV

They are very useful to identify the reasons for communication problems, anything from complete service interruptions to uncontrolled delays which can be as important in terms of service performance.



#### WIDEBAND LNB COMPATIBLE

Wideband LNBs deliver the entire vertical and horizontal satellite polarities (low and high band together) using two separate RF cables and an extended IF frequency range from 290 to 2,340 MHz. **Is your analyzer ready?** 



## Advanced satellite technology

#### Beacon-flyaways, SNG and VSAT ❖


Satellite BEACON signals can be clearly seen thanks to the 1 MHz SPAN and 10 kHz resolution filters.

Having the proper resolution filters is critical in some applications, **RANGERNeo** includes a very narrow 2 kHz filter available in terrestrial TV band.



#### **VCM / ACM modulation schemes**

VCM / ACM (Variable/Adaptative Coding and Modulation) allow changing the modulation parameters used in the same RF channel over time.




#### **IRG** descriptor identification

The IRG descriptor is an embedded code that is added to video links containing contact info, GPS coordinates, etc from the source signal to allow a quick troubleshoot of interferences in scenarios such as live transmissions of sports events.


Ivioae coae	QPSK CR=1/2 PILOTS=ON FRANCE=
Mode code	QPSK CR=2/3 PILOTS=ON FRAME=
Mode code	QPSK CR=3/4 PILOTS=ON FRAME=
Mode code	QPSK CR=4/5 PILOTS=ON FRAME=
Mode code	QPSK CR=5/6 PILOTS=ON FRAME=
Mode code	8PSK CR=3/5 PILOTS=ON FRAME=
Mode code	8PSK CR=2/3 PILOTS=ON FRAME=
Mode code	32APSK CR=3/4 PILOTS=ON FRAM






#### dCSS LNBs

Digital Channel Stacking Switch LNB can support several users on a single cable distribution system by allocating specific user bands for each of them. It is not possible to work with this type of LNB unless your field strength meter communicates using EN50494 (SATCR, UNICABLE) and EN50607 (dCSS, JESS, UNICABLE II) standard protocols.






#### **PLS - Physical Layer Scrambling**

The PLS index is a number generated by the broadcaster that must be properly decoded by the customer so that demodulation is possible. **RANGER***Neo* can also work with this type of signals.


#### **DVB-S2 multistream**

Advanced modulation techniques combine several independent transport streams into one single RF carrier. Selecting a specific TS is easy with your **RANGER**Neo using the ISI Filtering function.







## Advanced satellite technology



#### L-band spectrum analyzer **⊙**

RANGER Neo are more than just spectrum analyzers. They are truly multifunctional including characteristics such as 10 kHz to 1 MHz resolution bandwidths, high frequency accuracy, screen capture functionality, datalogger and 24/7 signal monitoring, spectrogram, remote control via webserver and SNMP, all in one box.









#### If you need 24/7 monitoring...

The **RANGER Neo** spectrum analyzers will help you identify signal impairments locally or remotely. They will offer you remote control, webserver, SNMP compatibility, video streaming capabilities or the possibility to set up alarms for automatic monitoring applications.

#### **Specifications**


- Frequency range: 5 to 2,500 MHz
- Input range: -90 dBm to +20 dBm (approx. 20 dBμV 130 dBμV)
- Resolution filters: 10 / 20 / 30 / 40 / 100 / 200 kHz, 1 MHz
- Span range: Full span, 1500, 1265, 850, 500, 250, 200, 100, 50, 20, 10, 2, 1 MHz
- Fast sweep time: 70 ms depending on span/RBW
- Amplitude sensitivity: 1, 2, 5, 10 dB/DIV
- Advanced features: Markers, Max/Min hold, Persistence, Trace averaging, RMS/PEAK, SAT IRG descriptor
- LNA/LNB power: 5/13/15/18 VDC, 22 kHz, DiSEqC, SATCR, dCSS
- Remote control: Ethernet port, webserver, SNMP
- Display: 7" touch screen colour TFT
- Battery time: More than 4 hours
- Size & Weight: 290 x 185 x 95 mm, 2.2 kgr (approx. 5 lbs)

#### **Applications**

- Teleport 24/7 monitoring
- SNG, VSAT, Flyaway antenna alignment
- SOTM Terminals (Satcom On-The-Move)
- Government and military SATCOM
- Oil rig & maritime satellite communications
- Beacon, TT&C (Telemetry, Tracking, and Command) signal location and monitoring
- Satellite, TV, CATV entertainment systems
- · VSAT system on-site and remote commissioning
- OB van antenna alignment and signal monitoring




### RANGERNeo TV ANALYZERS













#### **RANGER Neo +**



Web Server remote control

Merogram and Spectrogram

Fibre optics and GPS options

More than 4 hours battery time

DVB ISDB-T ATSC

Versions



#### **RANGER Neo 2**



IPTV analyzer

High resolution filters

TS-ASI input and output

Common Interface slot

Transport Stream recorder and player

Transport Stream analyzer

DVB ISDB-T

DVB ISDB-T ATSC

Versions



#### **RANGER Neo 3**



Network Delay Margin (DVB)

T2-MI analysis

GPS for drive test measurements

DVB ISDB-T version


ALL MODELS SUPPORT THE MOST RECENT BROADCASTING STANDARDS

UHD/4K DETECTION & MEASUREMENT

HbbTV INFORMATION

DAB+ CHANNEL PLAN






#### **LTE interference on CATV networks**

Some of the bands allocated to LTE are near or inside former television bands. For example band 20 (uplink 832-862 MHz; downlink 791-821 MHz). The **RANGERNeo** has special functions to help installers determine the level of activity in those bands and therefore anticipate potential interference problems

#### **Downlink and Uplink interference**

Downlink interference comes from the mobile phone base stations which are placed at fixed locations and are always on. This is not the case of Uplink interference which comes from the handheld devices and therefore it can be a lot more difficult to locate and mitigate.






### LTE Signals

#### LTE signals and channel repack

The use of Smartphones is widely spread all over the world. In order to meet user demand for bandwidth, mobile phone operators need to expand their networks, use more efficient transmission standards (LTE) and use part of the bandwidth historically assigned to TV broadcast services (channel repack in the US or digital dividend in Europe).






#### **M2M Machine to Machine applications**

Besides LTE interference measurements there is also an increasing need to look at the LTE signals themselves. This function can also be useful for Machine to Machine applications (electric car charging station, vending machine, wireless credit card reader...). One of the first problems you encounter is to make sure there is good signal coverage from the operator the system is working with.






# Dynamic echoes analysis & more

#### **DiSEqC** commands

Elementary DiSEqC commands are available from a drop-down list. They can be combined to form macros which can also be associated to a channel table.






#### Digital services database

**RANGER**Neo builds a list of the TV and RADIO services detected as it tunes the different digital channels. Besides tuning by frequency and channel It is then possible to select a specific service from the list.






# Transport stream analyzer & player \*

#### **Table analysis o**

This function shows every detail of the transport stream tables in real time on a tree diagram. This is an outstanding function which is normally only available in more expensive equipment. It is possible to navigate through the tree branches using the joystick or the touch screen functionality.






#### Record, analyze, decode and copy a Transport stream <sup>©</sup>

A function available for **RANGER***Neo* that enables the instrument to record the received TS in real time onto a a USB pendrive or on its internal memory. The recorded TS can also be decoded or analyzed.





## CATV network analysis

#### **SCAN**

CATV installers appreciate very much having a SCAN function on their analyzer for it allows them to check all the channel levels in a graphical way.






#### TILT

Using pilot generators as a reference, the TILT feature helps us to equalize the CATV network. We can detect as many as 4 pilots along the band from 6 – 999 MHz. The meter will calculate the level difference between the two most distant pilots and the tilt measurement (dB/MHz).







# Powerful datalogger and Task planner

#### **Datalogger and Test&Go**

The datalogger can perform channel power, carrier/noise, BER, MER... measurements automatically. It can also save information from the NIT table such as the network name or even the SID and names of the services in the mux under test. All this information is saved inside the meter and it can be downloaded to a USB memory or to a PC for further processing later on.





#### Task planner


This function allows to set-up a task list, both for screen capture or Datalogger acquisition, selecting when to start, a repetition rate and the number of times the selected task must be performed. The equipment can be switched off after setting all parameters and will itself wake-up, at the required time, to perform the planned tasks.






#### **Selective optical-to-RF converter**

TV&SAT distribution, is used more and more by operators because it allows them to benefit from the advantages of fibre optics to compete with FTTH service providers. The RF signal at the converter output can be analyzed, measured and decoded by the meter as one would usually do with any signal over copper wires.





#### **6 GHz RF auxiliary input**

The RANGERNeo optical fibre option comes along with 6 GHz RF auxiliary input which can be used among other applications for direct connection to wholeband LNB's with 5.45 GHz RF output. This auxiliary input covers three bands:

28.0 dB

Band I	From 2150 MHz to 3000 MHz
Band II	From 3400 MHz to 4400 MHz
Band III	From 4400 MHz to 6000 MHz





**GPS** This option turns the RANGERNeo into the perfect tool to perform signal coverage

"drive test" analysis functions. It can capture different kind of measurements embedding time/date and geographic

coordinates information.

Create 3D maps with your measurements

### Drive test GPS \*

#### Run your coverage analysis over one of multiple RF channels simultaneously

Once the drive test is completed, plot the coverage measurements overlayed in Google Earth (KML format), and generate the resulting reports in Exceland CSV formats.










TIME	LATITUDE	LONGITUDE	POWER (dBuV)	CN (dB)	OFFSET (kHz)
:45:33	41,4062683	2,2147717	32,70	16,50	-1,20
:45:36	41,4062683	2,2147717	35,40	19,30	-1,20
:45:39	41,4062683	2,2147717	35,40	19,40	-1,20
:45:42	41,4062683	2,2147717	31,70	15,10	-1,20
:45:45	41,4062683	2,2147717	33,00	14,40	-1,20
:45:48	41,4062683	2,2147717	32,70	14,30	-1,20
:45:51	41,4062683	2,2147717	30,70	10,90	0,00
:45:54	41,4062683	2.2147717	20.20	20.60	1.10
:45:57	41,4062683	D.	OM/ED mass.		
:46:00	41,4062683	]	OWER measu	rements	
:46:03	41,4062683				
:46:06	41,4062683		1021		
:46:09	41,4062683	-			A



#### **Creating reports**

All this information is saved automatically to either the internal meter's memory or to an external USB memory and can be transferred to a PC computer using a universal XML format. Once on the PC the data can be processed and presented in different ways among which overlaying the values on a map is the most interesting.


















#### DAB+ digital radio ○

DAB+ is an evolution of DAB (*Digital Audio Broadcast*) that among other differences uses AAC+ audio codec. It also includes Reed-Solomon error correction algorithm which makes it more robust against transmission impairments. **RANGER**Neo DAB option is compatible with both standards.





#### FM radio receiver and analyzer









#### **MPX Histrogram**

All parameters such as FM deviation sampling and refresh rates are set according to ITU-R SM.1268-2 and ITU-R SM.1268-4. Both normal and cumulative histograms are available.





#### **MPX Spectrum display**

Spectrum analysis of the MPX can have a variety of applications namely the detection of interferring signals which can not be seen otherwise.





### ADVANCED DAB OPTION FOR RANGER Neo 2 & RANGER Neo 3 ANALYZERS

The new advanced DAB option allows professional users to do DAB signal quality measurements and it includes many functions which are normally available in higher cost products only such as ETI recording, constellation diagram or echoes analysis.



# Advanced DAB/DAB+ option •

#### **ETI recording**

ETI stands for Ensemble Transport Interface and it may be described as the equivalent to the Transport Stream for DAB. It is possible to record ETI on the analyzer so that it can then be copied to an external device for further analysis.



#### 

#### **Dynamic echoes analysis**


DAB can also be operated in a Single Frequency Network (SFN) and therefore the dynamic echoes analysis becomes a handy function to have.





#### **Transmitter Identification Information TII**

Each transmitter operating in the area is identified by its TII. All TII details are displayed along with the spectral representation of the mux showing the PRS and Null symbols which can be easily identified by colour. A label can be edited and assigned to each transmitter.



PROMAX 12/03/2019 10	:57	AB 3/3	***				
Ensemble	0x10F0 NDR HH	Country Id	0x1				
Service	0xDF84 NDR Info Spezial			_			
Country Id	0xD	ECC	0xE0				
Content	Audio (1)	PTY	0x03 Information				
Component	0x00 NDR Info Spezial	Category	Primary				
SubChannel	0x07	Format	DAB+				
Protection	EEP 2-A	Bitrate	96 kbit/s				
Audio	HE-AAC, 48 kHz Stereo @ 96	kBit/s					
Language	0x00 Unknown						
adiotext (D	www.ndr.de/infospezial						
ETI locke	d: NDR HH [TII M:1 S:2]						
CH: 9A	DAB	Tool:	s Advanced				

#### Down to the smallest detail

It is also possible to display plenty of useful information about the DAB mux and audio ensembles such as Ensemble and Country IDs, ECC, PTY, Component and SubChannel information or even the detail of the Radiotext.





#### **Ethernet connectivity**

Ethernet and IP protocols are now the gold standards for remote control applications and **RANGER** *Neo* offers this functionality. Besides remote control the IP interface can be used to save or retrieve data from a PC, copy channel tables or installation information, dataloggers, screenshots, etc.





#### No running out of memory

There is a lot of information that **RANGER** *Neo* can store in its internal memory: Dataloggers, screenshots, signal monitoring files, etc. Its large storage capacity will make you think it's unlimited. However, files such as transport stream recordings can be very heavy. Storage capacity can also be extended to up to several Terabytes using a USB storage device.





**Perfect to be integrated into OB Vans** 

**RANGER** *Neo* rack and **PROWATCH** *Neo* systems are the solution needed by any professional involved in the reception and retransmission of satellite signals.

Including 24/7 permanent monitoring of satellite feeds, continuous evaluation of the transmission quality, system performance tracking... PROMAX systems feature remote control, webserver, SNMP compatibility, video streaming and alarms management.





#### Soft bag and hard case ⊙

A soft carrying bag and a heavy duty transport case are included as standard accessories.







# Extended connectivity features \*

#### **Transport stream input and output**

**RANGER**Neo can monitor and analyze streams coming out from satellite receivers, transport stream players, multiplexers, etc. Received transport stream signals can also be output to other devices.

#### **Common Interface**

The RANGERNeo includes a CI slot to interface with CAM modules available in the market and decode encrypted channels. The use of encryption is widely spread among television operators so this function is very useful.



















#### **HDMI™** interface

The RANGERNeo includes an HDMI™ output to interface with other High Definition equipment. It can also be very useful to check proper operation of the client's TV while on a service call. Everything that can be seen on the meter's screen is available through the HDMI™.

#### **Video input**

A RCA to jack adapter is also included for SD composite video input in all **RANGER***Neo* products.

#### **USB** and **Ethernet** connections

The **RANGERNeo** includes USB and Ethernet interfaces. The USB can be used to copy files to memory sticks for example. Remote control and web server functionality are available through the Ethernet port.



SPECIFICATIONS	RANGER Neo Lite	RANGER Neo +	RANGER Neo 2	RANGER Neo 3			
DIGITAL BROADCAST STANDARDS	DVB-T/T2, DVB-T2 lite DVB-C/C2 DVB-S/S2 DVB-S2 Multistream ISDB-T/TB DSS, ACM / VCM / CCM		Also includes: MPEG-TS	Also includes: DVB-T2-MI			
AUDIO CODECS	MPEG-1, MPEG-2, AAC, HE-A	AC, Dolby Digital, Dolby Digital Pl	lus				
VIDEO CODECS	MPEG-2, MPEG-4 / H.264, HE	VC / H.265					
INPUTS AND OUTPUTS	- Universal RF input 50/75 Ω - HDMI™ 1.4b output - IP interface for remote control - Analogue Video/Audio input - 2xUSB (Type-A) for data trans	efering	- ASI-TS input and output (BNC Female, 75 Ω) - IPTV multicast input (UDP / RTP, RJ45) - Common Interface slot				
FUNCTIONS	- Constellation diagram - LTE ingress test - Dynamic echoes analysis - StealthID (instant identification of tuning parameters) - 4K detection	PLS (Physical Layer Scrambling)     Ultra fast spectrum analyzer     (70 ms sweep time)     4K Frame Grabber     MAX and MIN hold     FM RDS radio measurement and decoding	- Screenshots and Datalogger for measurement reports - Beacon-Flyaways for SNG and VSAT - Wideband LNB - WiFi 2.4 GHz - OTT	- Service recording - Field strength measurement - Task planner - HbbTV information - DAB+ channel plan included			
ADDITIONAL FUNCTIONS		- Merogram - Spectrogram - Signal monitoring - Remote control (webControl) - MER by carrer - Video/Audio Streaming - SCAN + TILT - Shoulder attenuation	Also includes: - TS recording - TS analysis - IPTV multicast measurement and decoding	Also includes: - Network delay (DVB) - DVB-T2-MI analysis			
SPECTRUM ANALYZER Frequency margin  Measurement range Span Resolution bandwidths	From 250 to 2500 MHz (Satellit From 10 to 130 dBµV	Full / 500 / 200 / 100 / 50 / 20 / 10 MHz 2 kHz (terrestrial)					
MEASUREMENT MODE (please refer to STANDARDS section) Frequency Margin  DVB-T COFDM DVB-T2 Base and Lite COFDM DVB-C QAM DVB-C2 COFDM PAL, SECAM and NTSC FM radio DVB-S QPSK DVB-S2 QPSK, 8PSK, 16/32APSK DSS QPSK	1 MHz						
INTERNAL STORAGE	6 GB for measurement protocol	ls, screenshots and transport stre	am recordings				
PC CONNECTION (via ethernet interface)		NetUpdate 4 (free software) + Free and automatic firmware updates + User customised channel plans + Measurement reports and screenshots					
GENERAL	Hybrid operation: Touch screen DiSEqC 2.x generator (DiSEqC dCSS / SCD 2 (EN50607) and s	1.2 commands implemented)					
BATTERY	> 2 h	> 4 h (smart battery)					
HARD CASE	Optional	Included					

OPTIONS	RANGER Neo +	RANGER Neo 2	RANGER Neo 3		
GPS Coverage Analysis	Available	Available	Included		
Advanced DAB/DAB+ analyzer	Available	Available	Available		
Advanced FM radio analyzer	Available	Available	Available		
Rack assembly 19" 4U: 482 (W.) x 178 (H.) x 205 (D.) mm	Available	Available	Available		
OPM + Optical-to-RF converter + WiFi 5 GHz + LTE 2.6 GHz + 6 GHz RF input	Available	Available	Available		
WiFi 5 GHz + LTE 2.6 GHz + 6 GHz RF input	Available	Available	Available		

SPECIFICATIONS REFER TO EUROPEAN VERSION



### **RANGERNeo** TV analyzers

#### A new breed of analyzers for a new world

✓ Included Optional		Neo3	Neo 2	FIANOEIA G G G G G G G G G G G G G	Neo:	R. W.	M		
о ориона.			RAI	NGER	Neo			HD RANGER	
		3 2 +		+	Lite		Ultra Lite	Eco	
	DVB ISDB-T	DVB ISDB-T	ATSC	DVB ISDB-T	ATSC	DVB ISDB-T	ATSC	DVB	DVB
4K detection	✓	✓	✓	✓	✓	✓	✓	1	✓
HEVC H.265 decoder + 4K Frame Grabber	✓	✓	✓	✓	✓	✓	✓		
MPEG-2 and MPEG-4 H.264 decoder	✓	✓	✓	✓	✓	✓	✓	✓	✓
HbbTV Information	✓	✓	✓	✓	✓	✓	✓	✓	✓
Touch screen	✓	✓	✓	✓	✓	✓	✓		
Wide band LNB Compatibility (wbLNB)	✓	✓	✓	✓	✓	✓	✓		
2.4 GHz Wi-Fi analyzer	✓	✓	✓	✓	1	✓	✓		
1.8 GHz LTE	✓	✓	✓	✓	✓	✓	✓		
OTT	✓	1	✓	✓	✓	✓	✓		
Service recording	✓	✓	✓	✓	✓	✓	✓	✓	
HDMI output	1	1	1	1	1	1	✓		
Video/Audio input	1	1	<b>√</b>	✓	1	<b>✓</b>	<b>✓</b>	1	1
USB interface	2x Type A	2x Type A	2x Type A	2x Type A	2x Type A	2x Type A	2x Type A	1x Mini USB	1x Mini USB
Battery time	> 4 h	> 4 h	> 4 h	> 4 h	> 4 h	> 2 h	> 2 h	> 2 h	> 2 h
Resolution filter 100 kHz	✓	✓	<b>√</b>	✓	✓	<b>√</b>	<b>√</b>	✓	<b>√</b>
Resolution filters 200 kHz, 1 MHz	✓	1	1	1	1			1	
Resolution filters 2, 10, 20, 30, 40 kHz	√ ·	1	<b>√</b>						
Echoes analysis	1	1		1		✓		1	✓
Constellation diagram	✓	· /	✓	<b>√</b>	✓	1	✓	1	1
webControl and Video/Audio Streaming	<b>*</b>	<b>→</b>	<b>→</b>	<b>✓</b>	<b>✓</b>	•	•	· ·	
Spectrogram	<b>∀</b>	<b>→</b>	<b>→</b>	<b>∀</b>	<b>*</b>				_
DVB-T/T2: Merogram and MER by carrier	<b>∀</b>	<b>→</b>		<b>∀</b>	•				
SCAN + TILT	<b>✓</b>	<b>→</b>	✓	<b>✓</b>	1				_
SCAN + TIET	•	•	•	•	•				
IPTV analyzer	✓	1	✓						
TS-ASI input and output	✓	1	✓						
TS analysis and recording	✓	1	✓						
Common Interface (encrypted channels)	1	1	✓						
Shoulder attenuation measurement	1	✓	✓	1	1				
T2-MI	✓								✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓ ✓
Network delay Margin (DVB)	✓								
GPS for drive test	<b>√</b>	0	0	0	0				
Signal monitoring	✓	<b>✓</b>	<b>✓</b>	1	<b>✓</b>				
DAB/DAB+ channel plan	<b>✓</b>	<b>→</b>	<b>→</b>	<b>✓</b>	<b>*</b>	✓	✓	1	1
·		0		o	•	•	· ·	•	
Advanced DAB/DAB+ analyzer	0								
Advanced FM radio analyzer	0	0		0					
OPM + Optical-to-RF + WiFi 5G + LTE 2.6G + 6 G RF input	0	0	0	0	0				
WiFi 5 GHz + LTE 2.6 GHz + 6 GHz RF input	0	•	•	0	0				
ATSC standard			✓		✓		✓		
ISDB-T standard	1	✓	✓	1	1	✓	1		
DVB-T/T2 standard	1	√ ·	<b>√</b>	1	√ ·	<b>√</b>	✓	1	<b>✓</b>
DVB-S/S2, DSS and ACM/VCM standards	1	· /	1	✓	√ ·	· /	<b>√</b>	1	1
DVB-0/02, DGG and AGW/VGW standard	<b>✓</b>	<b>→</b>	· /	<b>✓</b>	1	· /	<b>√</b>	1	· /
DVB-C standard	<b>✓</b>	<b>→</b>	<b>→</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	<b>✓</b>	1	<b>-</b>
QAM annex B standard	<b>✓</b>	<b>✓</b>	<b>→</b>	<b>✓</b>	<b>✓</b>	<b>→</b>	<b>→</b>	•	,
	•	*	<b>→</b>	4	•	•			
PSIP analysis Closed Caption			<b>→</b>						
Giosea Caption									
Soft carrying bag	✓	✓	✓	✓	✓.	✓	✓	1	✓
Hard transport case	✓	✓	✓	✓	✓				