

WHITE RABBIT Z16

The reliable precise time fan-out for White Rabbit distribution



hw version >v5.0 (Low Jitter version)

The WR-Z16 is the reliable precise time fan-out for White Rabbit distribution on 1G Ethernet-based networks. It is a standalone device with 16 SFP connectors which provides sub-nanosecond accuracy time over plug-and-play fiber links.

The WR-Z16 provides White Rabbit, Synchronous Ethernet (SyncE) and very precise IEEE 1588 (PTP) and NTP interoperability in all its optical interfaces. Picosecond-level frequency distribution is available through digital clock.

The WR-Z16 incorporates seamless failover mechanisms which combine multi-source redundancy and holdover capabilities to ensure continued operation.

- Sub-nanosecond time accuracy
- 16 optical timing ports for WR, PTPv2 and NTP
- Multi-source time references
- Distance range over 80 km using fiber
- Linux-based WRZ OS
- Datacenter Optimized design
- Seamless Failover mechanisms
- Holdover capability
- Extended monitoring and management
- Redundant hot swappable power supply & fans
- Low jitter/phase noise frequency dissemination
- Built-in precise timing sources monitoring
- Support for HATI

Safran Electronics & Defense is with you every step of the way, building in the intelligence that gives you a critical advantage in observation, decision-making and guidance.

High Accuracy

The WR-Z16 implements the White Rabbit (WR) protocol, an high-accuracy extension of PTP based on SyncE, that allows to easily distribute sub-nanoseconds timing within Metro Area Network distances and beyond.

Interoperability

Placed at the top of the rack the WR-Z16 can distribute standard PTP IEEE1588-2008 and Synchronous Ethernet for the last hop through its 16x fiber ports using the most common profiles such as Telecoms profiles (G.8265.1, G.8275.1) & Power profiles (IEEE C37.238-2011 and IEEE/IEC 61850-9-3). It also provides NTP interoperability and 10MHz/PPS distribution.

Resiliency

The WR-Z16 incorporates seamless failover mechanisms to switch between multiple timing sources when a failure is detected, ensuring maximum availability and optimal synchronization performance even during the transitions. Additionally, an optional Holdover oscillator can be included to maintain high accuracy (1.5us < 24h) even if all timing references are down.

Low jitter enhancement

The low jitter/low phase noise version of the WR-Z16 includes improved clock circuitry in order to enhance the stability and accuracy of the timing outputs. As result of the improved performance, the WR-Z16 is able to meet the most demanding requirements in terms of time and frequency distribution.

Technical Specifications

Timing & Synchronization	
Multi-sources	<p><i>Failover mechanism to ensure continuous operation by switching over multiple timing sources in case of failure:</i></p> <ul style="list-style-type: none">• White Rabbit (accuracy <1ns)• External references (GNSS, Atomic Clocks)• PTP• NTP (Time of Day only) <p><i>Precise timing sources monitoring to evaluate the synchronization performance of multiple sources.</i></p>
WR	Supports HATI (Safran's High Accuracy IP Core)/ GM/ Master/ BC/ Slave modes
PTP IEEE 1588-2008	<p>Supports GM/ Master/ BC/ Slave modes, E2E/P2P, L2/ L3, Multicast/Unicast.</p> <p>Support for using PTP timing sources for WR fanout</p> <p>Supported Profiles:</p> <ul style="list-style-type: none">• Default• G.8265.1[1]• G.8275.1 [1]• IEEE C37.238-2011[1]• IEEE/IEC 61850-9-3[1]• Enterprise [1]• IEEE 1588-2019 HA [1]
SyncE	<ul style="list-style-type: none">• Available in all PTP ports• Supports key sections of the ITU-T G.8261, G.8262 & G.8264
NTP	<p>Supports Client & Server modes</p> <p>Supports NTP v2, v3 & v4</p> <p>Supports hardware timestamping</p> <p>Multiple servers configuration</p> <p>NTS support</p>
Holdover (optional)	Accuracy (learning 3 days from GNSS) below 1.5us @ 24h

[1]: PTP License not included in default package

Advanced Management

The WR-Z16 enables extensive monitoring via REST-API and SNMP, including the combination of smart alerts with traps. By providing templates, it facilitates its integration with third-party networking and monitoring tools. Moreover, it allows automatic topology discovery via LLDP and comprehensible remote logging through rsyslog.

Precise timing sources monitoring

The WRZ-OS incorporates a precise timing sources monitoring system which allow to evaluate the synchronization performance of multiple timing sources (WR, PTP, 1PPS+10MHz) received in the unit. Relevant metrics are computed and can be visualized in the WebUI. The monitoring data is collected and stored in a built-in database that can be exported using the integrated management tools

Enhanced Security

TACACS+/RADIUS have been integrated to enable remote authentication for networked access control through a centralized server. The secure version of most of the protocols such as SFTP, HTTPS, SNMPv3 has been implemented and a firewall has been incorporated to provide a robust system against malicious users.

Intuitive configuration

The new version of WRZ-OS introduces a complete web interface redesigned to provide an excellent user experience: By the means of timing presets, a complex configuration can be done in a few clicks. Simultaneously, the CLI tool has also been rethought to allow straightforward configuration from the terminal to advanced users.

Management & Communications	
Control	CLI & Web-GUI: HTTP(s)
Authentication	<ul style="list-style-type: none">• RADIUS• TACACS+
Monitoring	<ul style="list-style-type: none">• SNMPv3 (SNMPv2) + Traps with enterprise MIB• Smart-Alerts• REST-API
Network	<ul style="list-style-type: none">• SSHv2 + SFTP/SCP• HTTP(s)• DHCP• LLDP• Rsyslog

Security Features	
<ul style="list-style-type: none">• Authentication: RADIUS; TACACS+• Enable/Block protocols• SFTP/SCP: Securely transfers files to and from the device over an SSH session• SNMP v3: Remotely configure and manage over an encrypted connection• HTTPS support• Firewall configuration• Alert notifications via SNMP traps and email	

Specifications: 10MHz output		
Phase noise (dBc/Hz)	GM	Slave
1 Hz	-97.4	-95.8
10 Hz	-111.6	-109.8
100 Hz	-131.4	-131.5
1 kHz	-145.1	-145.2
10 kHz	-151.0	-150.9
100 kHz	-152.8	-153.0
ADEV		
@1s	8.52E-13	1.23E-12
@10s	1.09E-13	1.39E-13
@100s	1.55E-14	1.71E-14
@1000s	2.24E-15	2.95E-15
Signal waveform & Levels: LVTTL into 50 ohm, SMA		

Front Panel	
UART	RS232 Serial (RJ45 connector)
Ethernet	2x 100/1000 Base-T RJ45 (Management, NTP)
SFP Ports	16x 1GbE for timing distribution (WR/PTPv2/NTP selectable)
Timing I/O	<p>4x SMA connectors (3V @50Ω, TTL compatible):</p> <ul style="list-style-type: none"> • 10MHz OUT (LVTTL) • PPS OUT (LVTTL) • PPS IN (LVTTL) • 10MHz IN (TTL/CMOS/ECL/clipped sine)
Leds	<ul style="list-style-type: none"> • 3xLEDs for status information
Physical Specification	
Dimension	431 mm x 44 mm x 330 mm (Designed for EIA 19" rack)
Weight	3.0 kg
Color	White (Metallic)
Environmental Conditions	
Temperature	Operational: -10 to +50 °C Storage: -30 to +70 °C
Humidity	0% ~ 90% RH

Specifications: 1PPS output	
Accuracy when locked (WR or ext. reference)	< 1ns
Holdover (after 3 days locked to GNSS reference) *requires Holdover option	
After 4 hours	< 100 ns
After 8 hours	< 500 ns
After 24 hours	< 1.5us
Signal waveform & Levels: LVTTL into 50 ohm, SMA	

Back Panel Modules	
Power Supply	2x Redundant & Hot-swappable <ul style="list-style-type: none"> • 100-240VAC, 50-60 Hz • 50W (max. 80W) • -48 VDC modules available (optional)
Fan	2 x Swappable fan modules Airflow: blowing out
Agency approvals	
Certifications:	CE, TUV, FCC part 15 class A, RoHS, REACH, WEEE

Ordering information	
Base unit	P/N: EQP-WR-Z16-LJ-01
Product configuration	P/N
WR-Z16-LJ WR-Z16-LJ with Holdover WR-Z16-LJ with -48 VDC	EQP-WR-Z16-LJ-01 EQP-WR-Z16-LJ-02 EQP-WR-Z16-LJ-100

POWERED BY TRUST



safran-navigation-timing.com



April 21, 2025